

Xprinter®

Thermal Transfer/ Direct Thermal


XP-TT424B/TT434B

- Support thermal transfer and direct thermal printing
- Max print speed up to 127mm/s
- 8MB flash memory, 8MB SDRAM
- Ribbon core inner diameter: 0.5"
- Bartender special edition



XP-TT424B / TT434B

Thermal Transfer/ Direct Thermal



Model	XP-TT424B	XP-TT434B
Resolution	203 DPI	300 DPI
Print method	Thermal Transfer / Direct Thermal	
Print speed	127 mm (5") / s Max.	101.6 mm (4") / s Max.
Max.print width	108 mm (4.25")	
Max.print length	1778 mm (70")	

Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4-118mm (1.0"-4.6")
Media thickness	0.06~0.254 mm
Media core diameter	25.4 ~ 50.8 mm (1" ~ 2")
Ribbon length	Max.90m
Ribbon width	25.4mm-110mm (1"-4.3")
Label length	10 mm ~1778 mm
Label roll capacity	127 mm (5") OD(outer diameter)
Ribbon core inner diameter	12.7 mm (0.5 ")

Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
Interface	Standard:USB Optional:WIFI/Bluetooth/TF card
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor

Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°、90°、180°、270°
Emulation	TSPL、EPL、ZPL、DPL

Physical Features	
Dimension	246mm × 199mm × 168mm (D × W × H)
Weight	1.62kg

Reliability	
Print head life	30 km

Software	
Driver	Windows / Linux / Mac
SDK	Windows / Android / iOS

Power supply	
Input	AC 100-240V
Output	DC 24V, 2.5A

Options	
Factory Options	①Bluetooth module ②WiFi module ③Real clock ④Cutter
Dealer Options	① External paper roll holder ② Paper roll spindle ③ Extension board for external paper roll holder ④ Shipment waybill box

Environmental Conditions	
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

