

Stylish POS Terminal

TITAN S series

Style added on Performance
the new TITAN

- Intel Braswell Celeron N3160 or Bay Trail Celeron N2807 CPU
- Energy Efficient and Low Heat Generation Architecture
- Slim Display, Sleek Chassis and Small Footprint Design
- 15" LED LCD Display with True-Flat PCAP Touch
- IP55 dust and water Proof Front Panel
- Superior Serviceability and Easy Installation
- Fanless Operation and No Ventilation Hole
- Supporting M.2 SSD
- Microsoft Azure Certified



KEY FEATURE



OPTION



PERIPHERAL



SPECIFICATION

Model		TITAN-S100	TITAN-S200
System	CPU	Intel Celeron N2807 (Dual Core up to 2.16GHz)	Intel Celeron N3160 (Quad Core up to 2.24GHz)
	Storage	HDD: 320GB SSD: 256GB/128GB/64GB mSATA: 256GB/128GB/64GB	HDD: 320GB SSD: 256GB/128GB/64GB M.2: 256GB/128GB/64GB
	RAM	DDRIII 1 Slot (Up to 4GB)	DDRIII 1 Slot (Up to 8GB)
Display	LCD	15" LED Backlight LCD (1024 x 768)	
	Touch	PCAP Touch / 5W Resistive Touch	
Interface	Serial	3 Ports (RI/5V/12V BIOS Selectable) (1 Port: RS-422/485 (Jumper Selectable))	
	Parallel	1 Port (Factory option)	
	USB	2.0: 6 Ports	2.0: 4 Ports / 3.0: 2 Ports
	Ethernet	1 Port	
	VGA	1 Port	
	Drawer	1 Port / 2 CH(12V/24V Selectable)	
	Audio	1 Port (Line out)	
	MSR	1/2/3 Track Support (USB)	
Optional	Rear Display	VFD (20CH x 2Line, 256 x 32 Graphic) LCD (9.7", 15"(Touch Option))	
	Wall Mount	VESA Wall Mount	
	Stand	V Stand	
Software	OS	POSReady 7 / Windows 8.1 Industry Retail / Windows 10 IoT Enterprise	
Power Supply		DC 12V/5A(60W)	
Dimensions		379(W) x 264(H) x 362(D) mm	
Weight		6.0kg	
Color		Black + White, Black, White	
Certifications		CE / FCC / CB / cTUVus(NRTL) / RoHS	

* Without any prior notice, design and specification are subject to change.

INTERFACE VIEW

