PM351

SIMMERED DOWN TO THE ESSENTIALS: SIMPLE, INTUITIVE, AND STURDY HANDHELD TERMINAL

Straightforward and comfortable design

The form factor of PM351 maximizes the comfort of gripping it with one hand so that the several hours of working won't get you tired so much anymore. The 4.0in display with the capacitive touch is bright and daylight readable. Below the screen is the keypad for the easier yet more accurate data input, including the big orange scan button and power key: All within comfortable reach with one hand. While it is common to place the camera

back in most other devices, PM351's 8MP camera is placed on top of the device next to the scan engine, making the switch from scanning to taking pictures feel more natural.

Configure the PM351 just as you need it

PM351 offers 1D and two 1D/2D engine options. The keypad comes in two types: Numeric and Alpha Numeric to choose from. While 3GB RAM/32GB ROM is standard, you can opt for the 4GB/64GB option if you're using a particular solution that consumes lots of memory. In addition, in case your work involves a lot of outdoor tasks such as delivery, PM351 also comes with optional LTE connecting it to the network anywhere anytime.

Well-rounded performance and durability

The 2.0GHz octa-core processor runs the Android 11 operating system smoothly, supporting any modern Android solution. The PM351 is one of the few enterprise devices supporting Wi-Fi 6 (ready), enabling fast and secure data transfer. 4,800mAh battery gets the device going all day without charging. With the operating temperature ranging from -20°C to 60°C, IP65 water/dust resistance, and 1.5m (5ft) drops to concrete durability, PM351 is suitable for any harsh industrial setting.

Industries

Transport & Logistics Manufacturing & WMS

Accessories

Standard

AC/DC Power Adaptor Country Plug

LCD Protection Film USB-C cable

Standard Battery (4,800mAh)

Wristband Stylus

Optional

Single Slot Cradle

Dual Slot Cradle

*Connect up to 3 Dual Slot Cradles to charge up to 6 devices at a time

4 Slot Battery Charger

Pistol Grip

Pistol Grip Wristband



















🗊 🗊 😩 🍥

F2 F3 F4

11 (2) (0)

7 8 9

4 5 6



















PM351-DS01.02 -EN // PRE-SALES USE ONLY - SPECIFICATIONS MAY CHANGE

PM351

PERFORMANCE CHARACTERISTICS

Main-Processor

Qualcomm® Octa-core @2.0GHz

Operating System

Google Android Android 11 (upgradable)

(CTS & GMS certified) FOTA (Firmware Over The Air) update

Memory and Storage

3GB / 32GB or 4GB / 64GB (optional) RAM / ROM Supports up to 512GB using $\,$ ExFAT file system Micro SD

SIM 1 Micro SIM card slot

Proximity sensor Sensor Light ambient sensor

Acceleration and Gyro sensor

PHYSICAL CHARACTERISTICS

200mm X 70mm X 36.5mm

7.87in X 2.75in X 1.43in

320g / 11.2oz Weight

4.0", IPS panel (480 x 800 pixel), WVGA Display

LED backlight

Daylight readable (min 500 nits)

Wideviewing angle Multi-touch capacitive Dragontrail™ glass

Power 3.63V, 4,800mAh Li-ion rechargeable

Keypad

2 keypad options Numeric or Alpha numeric

Voice and Audio Built-in microphone

Speaker

Standard USB 2.0 Type C OTG Communications

Pogo pin 2 on the bottom: charging Pogo pin 2 on the back: Gun Trigger

Notification 2 x dual color LEDs for Power and warning

indication, vibration, beep

GLOBAL POSITIONING SYSTEM

WiFi SKU: No GPS

Phone SKU: Qualcomm GPS

Corporate Headquarters

pm_sales1@pointmobile.com

Point Mobile Co., Ltd.

+82 2 3397 7870

GNSS Receiver Support for GPS, GLONASS, Galileo and Beidou

WIRELESS

Wireless WAN

WCDMA B1/2/5/6/8/19

LTE TDD

Wireless LAN

Radio IEEE 802.11 a/b/g/n/ac/ax(ready)/d/h/i/k

Data Rates 2.4GHz: 802.11b/g/n: Up to 150Mbps

Operating

Channel

Bandwidth

WEP (40 or 104bit) Security and Encryption

WPA/WPA2 Enterprise (TKIP/AES)

WPA3 Personal (SAE)

Enhanced Open (OWE) PEAP (MSCHAPv2, GTC)

TLS, TTLS (PAP, MSCHAP, MSCHAPv2, GTC) PWD, SIM, AKA, AKA', LEAP

CCKM, 802.11r Fast Roam

BLE support

DATA CAPTURE

Integrated Barcode Reader

scanner

1D/2D barcode

8MP with LED flash (optional) Top

NFC (Near Field Communication)

(NFC-IP MODES)

P2P Active (106 To 424 kbps) Initiator and

Target, P2P Passive (106 To 424 kbps)

Initiator and Target

ISO/IEC 14443 A, ISO/IEC 14443 B Reader

USER ENVIRONMENT

MIL-STD 810G for multiple 1.5m (5ft) drops on concrete over the operating temperature

500 cycle (1,000hits) at 1m / 3.3ft per IEC Tumble 60068-2-32 specification

Point Mobile Europe GmbH europe@pointmobile.com

China Headquarters

Dropping 10,000 times from 0.2 m high to the wood floor

PC tool for provisioning Point Mobile

Android devices. With Scan2Stage, IT administrator can prepare the settings of

the device and make QR code for

Kiosk application for Point Mobile

execution via EmKiosk to increase

productivity and prevent distractions

PDA becomes a hotspot server and

sends its backup file to nearby client devices to clone the settings.

Solution for restoring the devices to the

scope of the operator's system

same settings with no internet connection. With Direct Clone, a Master

PULS - ANDROID UPDATE & SECURITY

PULS is Point Mobile's lifetime solution, which extends the

up to seven years after a product launch.

Patches, Updates & Lifetime Support

or contact your regional sales representative.

defective materials and manufacturing defects.

For the further inquiry, please contact: service@pointmobile.com

WARRANTY

Stay up-to-date with the latest updates for 7 years

PULS comes free of charge for security patches & updates

Get the latest Android version and its newest features

Conveniently update your devices in the field by FOTA

For further information, please visit www.pointmobile.com

Subject to the Terms and Conditions, PM351 carries 1 (one)

year-warranty period from the date of purchase against the

life cycle of Android-based Point Mobile enterprise devices to

devices. IT administrator can restrict the

Scan2Set.

±15 kV air discharge

REGULATORY APPROVALS

ENTERPRISE SOLUTION

AND COMPLIANCE

SOTI, Airwatch, Teamviewer

EmKit

Scan2Stage

EmKiosk

Direct Clone

±8 kV direct discharge

Operating Repetitive Drop

(Sealing)

Electrostatic

Discharge

TBA

Rain / Dust Proof

Point Mobile China info@pointmobile.com.cn +86 755 8869 1169



EDGE/GPRS/GSM 900/1800 LTE FDD B1/2/3/5/7/8/17/20

/r/v, 1x1 MU-MIMO

5GHz: 802.11a/n/ac: Up to 433Mbps

1 to 13 (2412~2472MHz) 36 to 165 (5180~5825MHz)

20. 40. 80 MHz

WPA/WPA2 Personal (TKIP, AES)

WPA3 Enterprise (AES) WPA3 Enterprise 192-bit mode (GCMP 256)

Wireless PAN

Bluetooth Integrated Bluetooth Class I, Ver. 5.1

SE965 1D barcode

SE4100 or SE4710

scanner

Camera

NFC-Forum

Reader For NFC Forum (Tag Types 1 To 5),

(PCD - VCD)

ISO/IEC 15693, Mifare Classic 1K/4K Mifare DESFire, Mifare UltraLight®, Sony FeliCa

-20°C to 60°C (with 1D scan engine) Operating Temperature -20°C to 50°C (with 2D scan engine) Humidity 95% Non-condensing Drop

Europe Headquarters

+49 6196 777 3666

+1 425 780 4452

NA Headquarters

Point Mobile Americas LLC

info@pointmobileamericas.com